



PRODUCT DESCRIPTION

- (2) 8" X 11" X 4" 4.1-lb recycled plastic bases.
- (16) 1/2" X 1" UNC hex-head hot-dip galvanized steel bolts, (4) #14-1/4" X 1" hex washer head screws, (4) 3/8" electrogalvanized steel square flat washers, (2) 10" X 1-5/8" X 13/16" 14-gage electrogalvanized slotted steel struts, (16) 1/2" UNC hot-dip galvanized channel nuts, (4) 4-hole 90° 3-1/2" X 4-1/8" - 1/4" steel brackets.

ACCESSORY ITEMS

- 12" X 12" base pad.

KEY INFORMATION

- Base Material: Recycled plastic regrind typically 80-90% polyolefins, predominantly high-density polyethylene and polypropylene.
- Coloration will vary due to recycled plastic feedstock.
- Ultimate load shall not exceed 2,500 lbs. per base. To avoid damage to the roof, rooftop loading is not to exceed maximum allowable load per roofing manufacturer.
- For maximum membrane protection, the use of a base pad or other sacrificial material between the bases and the finished roof surface is recommended.
- Space supports per building code for component being supported. Recommended spacing not to exceed 10 foot centers or maximum allowable weight per roofing and pipe manufacturer.

WARRANTY INFORMATION

- 2 year limited warranty.

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of Rooftop Sleeper Support, Inc. Any reproduction in part or as a whole without written permission of Rooftop Sleeper Support, Inc. is prohibited. Rooftop Sleeper Support is a division of MIRO Industries Inc.

ISSUE DATE

30.MAY.17

SADDLE SUPPORT BASE KIT